



High Performance Products

25-44 Borough Place • Woodside, NY 11377 • 718.278.7900 • [email:info@super-](mailto:info@super-tek.com)

[tek.com](http://www.super-tek.com)

# Acrylic Grout Additive MSDS

## SECTION I – PRODUCT IDENTIFICATION

**Super-Tek Products, Inc.**

**25-44 Borough Place, Woodside, NY 11377**

**Telephone #: 718-278-7900**

**Emergency Phone #: 718-278-7900**

**Generic ID:** Latex Based Admixture

**Product Identity:** Acrylic Grout Additive

**Date Prepared:** 1/1/02

## SECTION II – INGREDIENTS & HAZARDOUS COMPONENTS

<b>Ingredient Name</b>	<b>CAS Number</b>	<b>Percent</b>	<b>Exposure Limits</b>
Latex Polymer	N/A	7-10	5000 ppm (TLV)

\* Other Non-Hazardous Ingredients considered a Trade Secret

## SECTION III – PHYSICAL DATA

**Initial Boiling Point:** 212°F.  
**Vapor Pressure:** Same as water.  
**Vapor Density (Air=1.0):** Same as water.  
**Specific Gravity:** 1.01.  
**Percent Volatiles:** 90-93.0%.  
**VOC GL:** 0%.

## SECTION IV – FIRE AND EXPLOSION DATA

**Flash Point:** N/A.  
**Explosive Limit (Product):** N/A.  
**Extinguishing Media:** None to avoid.  
**SPECIAL FIRE FIGHTING PROCEDURES:** None.  
**UNUSUAL FIRE & EXPLOSION HAZARDS:** None.

## SECTION V – HEALTH HAZARD DATA

**Permissible Exposure Level:** N/A.  
**Threshold Limit Value:** N/A.

### EFFECTS OF EXPOSURE:

**Skin:** Possible mild irritation.  
**Eyes:** Possible mild irritation.  
**Inhalation:** None known.

### FIRST AID:

**Skin:** Soap and water.  
**Eyes:** Flush with water, lifting upper and lower lids occasionally.  
**Inhalation:** If affected, remove individual to fresh air. Use only in well ventilated areas.  
**Ingestion:** Do not induce vomiting. Call physician or transport to an emergency facility.

## SECTION VI – REACTIVITY DATA

**Stability:** Stable.

**Incompatibility:** None.

**Hazardous Decomposition:** None.

**Hazardous Polymerization:** None.

**Conditions to Avoid:** None Known.

## SECTION VII – SPILL OR LEAK PROCEDURES

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:** Absorb liquid on paper, vermiculite, floor absorbent, or other absorbent material. Solidified materials accepted for landfill disposal in most locations. Check all local, state, and federal regulations.

## SECTION VIII – PROTECTIVE EQUIPMENT

**Ventilation:** Open all available windows and entrances to insure good ventilation.

**Respirator Protection:** None needed.

**Protective Gloves:** If sensitive.

**Eye protection:** Wear glasses or protective goggles to avoid splashes.

**Other Protective Equipment:** None required.

**WASH HANDS THOROUGHLY WITH SOAP AND WATER.**

## SECTION IX – SPECIAL PRECAUTIONS

Protect from freezing. Use only in applications as stated on the label. Do not take internally. Close container after each use. Avoid skin and eye contact.

Ventilation with fresh air, including open doors and windows should be observed during any flooring installation. Operate HVAC systems at 100% fresh air intake before, during and after installation to eliminate lingering odors or particulate matter.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with company or not. Recipients are advised to confirm in advance of need that the information is current, applicable and suitable to their circumstances.

## **KEEP OUT OF REACH OF CHILDREN**

---

All material at this site is © Copyright 2003 Super-Tek Products, Inc. and may not be reproduced without written permission.

*rev. 12/2003*